



UMBOTRON.COM

WHEN QUALITY MATTERS

JUMBO J26 & JUMBO J28X PLATFORM TRAILER



info@jumbotron.com



877-794-2220 x 101



Jumbotron.com

JUMBO J26 PLATFORM



info@jumbotron.com



877-794-2220 x 101



Jumbotron.com

Specification

Trailer appearance

Gross weight	3700kg
Chassis	German-Made AIKO
Breaking	Hydraulic breaking
Maximum screen size	6720mm × 3840mm
Max speed	100Km/h
Axle	2 axles, Bearing 5000kg

Power Parameter

Input voltage	96-264V
Output voltage	48V
Inrush current	65A
Maximum and average power consumption	150wh/m ² , 50/60 Hz

Battery Pack

Dimension	730mm*430mm*237mm*2pcs
Battery specification	51.2V 300Ah*2pcs

Electric Charging Machine

Model	Meanwell NPB-1200
Dimension	250*158*67mm

Inverter

Power	3000W
-------	-------

Sound System

Power amplifier	1000W
Speaker	200W*4



Hydraulic System	
Wind-proof level	Level 8
Supporting legs	Stretching distance 300mm
Hydraulic Lifting and folding system	Lifting Range 4650mm, bearing 3000kg
Fold the ear screens on both sides	4pcs electric pushrods folded
Rotation	Electric rotation 360 degrees

Others	
Wind speed sensor	Alarm with mobile APP

Notes	
Maximum trailer weight	5000 kg
Trailer width	2,1 m
Maximum Screen height (top)	7.5 m
Galvanized chassis made according to DIN EN 13814 and DIN EN 13782	
Anti slip and waterproof floor	
Hydraulic, galvanized and powder coated telescopic mast with automatic mechanical safety locks	
Hydraulic pump with manual control (knobs) to lift LED screen up	3 phase
360° screen manual rotation with mechanical lock	
Auxiliary emergency manual control - handpump - screen folding without power according to DIN EN 13814	For very large screens it may be necessary to put out the outriggers for transport (you can take it to the car pulling the trailer).



Specification

Trailer appearance

Gross weight	4000kg
Chassis	German-Made AIKO
Breaking	Hydraulic breaking
Maximum screen size	7000mm × 4000mm
Max speed	100Km/h
Axle	2 axles, Bearing 5000kg

Silent Generator Group

Dimension	1300x750x1020mm
Power	15KW GAS generator set
Voltage and frequency	415V, 50/60 Hz
Engine	R999
Motor	GPI184ES
Noise	66dBA/7m
Others	electronic speed regulation

Sound System

Power amplifier	1000W
Speaker	200W*4

Hydraulic System

Wind-proof level	Level 8
Supporting legs	Stretching distance 300mm
Hydraulic Lifting and folding system	Lifting Range 4650mm, bearing 3000kg
Fold the ear screens on both sides	4pcs electric pushrods folded
Rotation	Electric rotation 360 degrees



Others

Wind speed sensor

Alarm with mobile APP

Notes

Maximum trailer weight

5000 kg

Trailer width

2,1 m

Maximum Screen height (top)

7.5 m

Galvanized chassis made according to DIN EN 13814 and DIN EN 13782

Anti slip and waterproof floor

Hydraulic, galvanized and powder coated telescopic mast with automatic mechanical safety locks

Hydraulic pump with manual control (knobs) to lift LED screen up

3 phase

360° screen manual rotation with mechanical lock

Auxiliary emergency manual control - handpump - screen folding without power according to DIN EN 13814

For very large screens it may be necessary to put out the outriggers for transport (you can take it to the car pulling the trailer).



info@jumbotron.com



877-794-2220 x 101



Jumbotron.com